

L

鎢鋼鑽頭 Carbide Drill



鎢鋼鑽頭識別系統、規格圖標指南 L02
Carbide Drill Identification System、Specification Icon Guide

鎢鋼鑽頭、中心出水鎢鋼鑽頭、鎢鋼平鑽切削參數 L34
The Cutting Data For Carbide Drill and Carbide Drill With Coolant and Carbide Flat Drill

鎢鋼鉸刀識別系統、規格圖標指南 L35
Carbide Reamer Identification System、Specification Icon Guide

鎢鋼鉸刀切削參數 L38
The Cutting Data For Carbide Reamer


◎ 鎢鋼鑽頭系列 Carbide Drill Series

 ME20 L03—L12
 SPE20 L13—L20


◎ 中心出水鎢鋼鑽頭系列 Carbide Drill With Coolant Series

 SPEC20 L21—L29

◎ 鎢鋼平鑽系列 Carbide Flat Drill Series

 EI20 L30—L33


◎ 鎢鋼鉸刀系列 Carbide Reamer Series

 RL-SMM30000 L36—L38

鎢鋼鑽頭識別系統

Carbide Drill Identification System

M E C 2 0600 S 03 D4



1 材質 Grade

記號 Symbol	材質 Grade
E	E300
G	G300
H	H300
M	M500
P	P500
W	W500
SM	SM600
SW	SW600
SP	SP600

2 尖端角 Point Angle

記號 Symbol	尖端角 Point Angle
A	118°
B	120°
C	130°
D	135°
E	140°
F	142°
G	145°
H	150°
I	180°

5 切削直徑 Cutting Diameter

說明 Explanation
ex : 0220 : 2.2mm 2225 : 22.25mm

7 加工倍數 Processing Multiple

7 加工倍數 Processing Multiple

加工深度倍數 Processing Depth Multiple	02、03、04、05、08
深孔倍數 Deep Hole Multiple	10、12、15、20、25、30

6 刀尖形狀 Drill Tip Shapes

記號 Symbol	說明 Explanation
S型	一般通用 General
X型	深孔及較硬材用 For Deep Holes And Harder Materials
XS型	深孔用 For Deep Holes

8 其他 Other

記號 Symbol	說明 Explanation	記號 Symbol	說明 Explanation
A	同柄徑 (小數點) Decimal Point of Shank (Same Shank)	TXX	錐度 Taper
DXX	特殊柄徑 Special Shank Diameter	LIXXX	特殊刃長 Special Flute Length

規格圖標指南


Specification Icon Guide

圖標 Icon	說明 Explanation	圖標 Icon	說明 Explanation
MG	超微粒子超硬合金 Micro Grain Carbide	AlTiN TiSiN	AlTiN 鋁鈦氮塗層 TiSiN 鈣鈦塗層
CO 10% CO 12%	含鈷量 Cobalt Content	E 300 G 300 H 300	材質 Grade
HRC <55 HRC <60	可被切削材硬度 Hardness Of Workpiece	M 500 P 500 W 500	
h8	刃徑公差 Tolerance Of Diameter	SM 600 SW 600 SP 600	
DIN 6537	符合DIN6537規範 Conform To DIN6537 Specifications	2D 3D 5D	

ME 20 系列 鎢鋼鑽頭 Carbide Drill

圓棒採用含鈷量12%超微粒硬質合金，全新Al-TiN鍍鈦塗層
泛用性廣，可適用：合金鋼、不鏽鋼、鑄鐵等材質加工。

The Carbide rod is made of a high-performance alloy with a cobalt content of 12% and ultrafine particles, along with gold, and features a new Al-TiN titanium coating. It has wide applicability and can be used for materials such as alloy steel, stainless steel, and cast iron.



鑽尖結構優化設計，提升切削排屑性能。
Optimized design of drill tip structure
to improve cutting performance.



獨特雙刃帶設計，提升加工穩定性
延長加工使用時間。

Unique double-edged belt design
improves processing stability and
prolongs processing time.

適用材質
Material

合金鋼
Alloy Steel

不鏽鋼
Stainless steel


鑄鐵
Cast Iron

高剛性、耐磨耗、耐高溫
High rigidity, Wear resistance,
High temperature resistance

尺寸齊全
歡迎詢問

Welcome to inquiry,
a complete range of
specifications are in stock

採用全新進口五軸刀具研磨機生產，研磨尺寸精準且穩定
Produced by a brand-new imported five-axis cutter
grinder with precise and stable grinding size.

ME20 鎢鋼鑽頭
Carbide Drill新規格上市
New Specification Arrival


	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	ME20150S05	●	1.5	12	0.3	4	9	28	58	
NEW	ME20160S03	●	1.6	9	0.3	4	6	28	58	
NEW	ME20180S03	●	1.8	9	0.3	4	6	28	58	
	ME20200S03	●	2	13	0.4	4	9	28	58	
	ME20200S05	●	2	18	0.4	4	14	28	58	
	ME20210S03	●	2.1	13	0.4	4	9	28	58	
	ME20210S05	●	2.1	18	0.4	4	14	28	58	
NEW	ME20214S03	●	2.14	13	0.4	4	9	28	58	
NEW	ME20218S03	●	2.18	13	0.4	4	9	28	58	
	ME20220S03	●	2.2	13	0.4	4	9	28	58	
	ME20220S05	●	2.2	18	0.4	4	14	28	58	
NEW	ME20225S03	●	2.25	13	0.4	4	9	28	58	
	ME20230S03	●	2.3	13	0.4	4	9	28	58	
	ME20230S05	●	2.3	18	0.4	4	14	28	58	
	ME20240S03	●	2.4	17	0.4	4	12	28	58	
	ME20240S05	●	2.4	22	0.4	4	17	28	58	
	ME20245S03	●	2.45	17	0.4	4	12	28	58	
	ME20245S05	●	2.45	22	0.4	4	17	28	58	
	ME20250S03	●	2.5	17	0.5	4	12	28	58	
	ME20250S05	●	2.5	22	0.5	4	17	28	58	
	ME20255S03	●	2.55	17	0.5	4	12	28	58	
	ME20260S03	●	2.6	17	0.5	4	12	28	58	
	ME20260S05	●	2.6	22	0.5	4	17	28	58	
	ME20270S03	●	2.7	17	0.5	4	12	28	58	
	ME20270S05	●	2.7	22	0.5	4	17	28	58	
	ME20280S03	●	2.8	17	0.5	4	12	28	58	
	ME20280S05	●	2.8	22	0.5	4	17	28	58	
	ME20290S03	●	2.9	17	0.5	4	12	28	58	
	ME20290S05	●	2.9	22	0.5	4	17	28	58	
	ME20300S03D4	●	3	20	0.5	4	14	36	62	
	ME20300S03	●	3	20	0.5	6	14	36	62	
	ME20300S05D4	●	3	28	0.5	4	23	36	66	
	ME20300S05	●	3	28	0.5	6	23	36	66	

※ 請接下頁。 ※ Continued on next page.

產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
		DC	LCF	PL	DCON	LU	LS	OAL	
ME20310S03D4	●	3.1	20	0.6	4	14	36	62	
ME20310S03		3.1	20	0.6	6	14	36	62	
ME20310S05D4	●	3.1	28	0.6	4	23	36	66	
ME20310S05	●	3.1	28	0.6	6	23	36	66	
ME20320S03D4	●	3.2	20	0.6	4	14	36	62	
ME20320S03	●	3.2	20	0.6	6	14	36	62	
ME20320S05D4	●	3.2	28	0.6	4	23	36	66	
ME20320S05	●	3.2	28	0.6	6	23	36	66	
ME20325S03D4		3.25	20	0.6	4	14	36	62	
ME20325S03	●	3.25	20	0.6	6	14	36	62	
ME20330S03D4	●	3.3	20	0.6	4	14	36	62	
ME20330S03		3.3	20	0.6	6	14	36	62	
ME20330S05D4	●	3.3	28	0.6	4	23	36	66	
ME20330S05	●	3.3	28	0.6	6	23	36	66	
ME20340S03D4	●	3.4	20	0.6	4	14	36	62	
ME20340S03	●	3.4	20	0.6	6	14	36	62	
ME20340S05D4	●	3.4	28	0.6	4	23	36	66	
ME20340S05	●	3.4	28	0.6	6	23	36	66	
ME20350S03D4	●	3.5	20	0.6	4	14	36	62	
ME20350S03	●	3.5	20	0.6	6	14	36	62	
ME20350S05D4	●	3.5	28	0.6	4	23	36	66	
ME20350S05	●	3.5	28	0.6	6	23	36	66	
ME20355S03	●	3.55	20	0.6	6	14	36	62	
ME20355S03D4	●	3.55	20	0.6	4	14	36	62	
ME20360S03D4	●	3.6	20	0.7	4	14	36	62	
ME20360S03		3.6	20	0.7	6	14	36	62	
ME20360S05D4	●	3.6	28	0.7	4	23	36	66	
ME20360S05		3.6	28	0.7	6	23	36	66	
ME20365S03	●	3.65	20	0.7	6	14	36	62	
ME20370S03D4	●	3.7	20	0.7	4	14	36	62	
ME20370S03		3.7	20	0.7	6	14	36	62	
ME20370S05D4	●	3.7	28	0.7	4	23	36	66	
ME20370S05	●	3.7	28	0.7	6	23	36	66	
ME20380S03D4	●	3.8	24	0.7	4	17	36	66	
ME20380S03	●	3.8	24	0.7	6	17	36	66	
ME20380S05D4		3.8	36	0.7	4	29	36	74	
ME20380S05		3.8	36	0.7	6	29	36	74	
ME20390S03D4	●	3.9	24	0.7	4	17	36	66	
ME20390S03	●	3.9	24	0.7	6	17	36	66	
ME20390S05D4	●	3.9	36	0.7	4	29	36	74	
ME20390S05	●	3.9	36	0.7	6	29	36	74	
ME20400S03D4	●	4	24	0.7	4	17	36	66	

※ 請接下頁。 ※ Continued on next page.

ME20 鎢鋼鑽頭
Carbide Drill




新規格上市
New Specification Arrival

產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
		DC	LCF	PL	DCON	LU	LS	OAL	
ME20400S03	●	4	24	0.7	6	17	36	66	
ME20400S05D4		4	36	0.7	4	29	36	74	
ME20400S05	●	4	36	0.7	6	29	36	74	
ME20410S03	●	4.1	24	0.7	6	17	36	66	
ME20410S05	●	4.1	36	0.7	6	29	36	74	
ME20420S03	●	4.2	24	0.8	6	17	36	66	
ME20420S05	●	4.2	36	0.8	6	29	36	74	
ME20430S03	●	4.3	24	0.8	6	17	36	66	
ME20430S05	●	4.3	36	0.8	6	29	36	74	
ME20440S03	●	4.4	24	0.8	6	17	36	66	
ME20440S05	●	4.4	36	0.8	6	29	36	74	
ME20450S03	●	4.5	24	0.8	6	17	36	66	
ME20450S05	●	4.5	36	0.8	6	29	36	74	
ME20455S03	●	4.55	24	0.8	6	17	36	66	
ME20455S05	●	4.55	36	0.8	6	29	36	74	
ME20460S03	●	4.6	24	0.8	6	17	36	66	
ME20460S05	●	4.6	36	0.8	6	29	36	74	
ME20470S03	●	4.7	24	0.9	6	17	36	66	
ME20470S05	●	4.7	36	0.9	6	29	36	74	
ME20480S03	●	4.8	28	0.9	6	20	36	66	
ME20480S05	●	4.8	44	0.9	6	35	36	82	
ME20490S03	●	4.9	28	0.9	6	20	36	66	
ME20490S05	●	4.9	44	0.9	6	35	36	82	
ME20500S03	●	5	28	0.9	6	20	36	66	
ME20500S05	●	5	44	0.9	6	35	36	82	
ME20510S03	●	5.1	28	0.9	6	20	36	66	
ME20510S05	●	5.1	44	0.9	6	35	36	82	
ME20520S03	●	5.2	28	0.9	6	20	36	66	
ME20520S05	●	5.2	44	0.9	6	35	36	82	
ME20530S03	●	5.3	28	1	6	20	36	66	
ME20530S05	●	5.3	44	1	6	35	36	82	
ME20540S03	●	5.4	28	1	6	20	36	66	
ME20540S05	●	5.4	44	1	6	35	36	82	

※ 請接下頁。 ※ Continued on next page.

產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
		DC	LCF	PL	DCON	LU	LS	OAL	
ME20550S03	●	5.5	28	1	6	20	36	66	
ME20550S05	●	5.5	44	1	6	35	36	82	
ME20560S03	●	5.6	28	1	6	20	36	66	
ME20560S05	●	5.6	44	1	6	35	36	82	
ME20570S03	●	5.7	28	1	6	20	36	66	
ME20570S05	●	5.7	44	1	6	35	36	82	
ME20580S03	●	5.8	28	1.1	6	20	36	66	
ME20580S05	●	5.8	44	1.1	6	35	36	82	
ME20590S03	●	5.9	28	1.1	6	20	36	66	
ME20590S05	●	5.9	44	1.1	6	35	36	82	
ME20600S03	●	6	28	1.1	6	20	36	66	
ME20600S05	●	6	44	1.1	6	35	36	82	
ME20610S03	●	6.1	34	1.1	8	24	36	79	
ME20610S05	●	6.1	53	1.1	8	43	36	91	
ME20620S03	●	6.2	34	1.1	8	24	36	79	
ME20620S05	●	6.2	53	1.1	8	43	36	91	
ME20630S03	●	6.3	34	1.1	8	24	36	79	
ME20630S05	●	6.3	53	1.1	8	43	36	91	
ME20640S03	●	6.4	34	1.2	8	24	36	79	
ME20640S05	●	6.4	53	1.2	8	43	36	91	
ME20650S03	●	6.5	34	1.2	8	24	36	79	
ME20650S05	●	6.5	53	1.2	8	43	36	91	
ME20660S03	●	6.6	34	1.2	8	24	36	79	
ME20660S05	●	6.6	53	1.2	8	43	36	91	
ME20670S03	●	6.7	34	1.2	8	24	36	79	
ME20670S05	●	6.7	53	1.2	8	43	36	91	
ME20680S03	●	6.8	34	1.2	8	24	36	79	
ME20680S05	●	6.8	53	1.2	8	43	36	91	
ME20690S03	●	6.9	34	1.3	8	24	36	79	
ME20690S05	●	6.9	53	1.3	8	43	36	91	
ME20700S03	●	7	34	1.3	8	24	36	79	
ME20700S05	●	7	53	1.3	8	43	36	91	
ME20710S03	●	7.1	41	1.3	8	29	36	79	
ME20710S05	●	7.1	53	1.3	8	43	36	91	
ME20720S03	●	7.2	41	1.3	8	29	36	79	
ME20720S05	●	7.2	53	1.3	8	43	36	91	
ME20730S03	●	7.3	41	1.3	8	29	36	79	
ME20730S05	●	7.3	53	1.3	8	43	36	91	
ME20740S03	●	7.4	41	1.3	8	29	36	79	
ME20740S05	●	7.4	53	1.3	8	43	36	91	
ME20750S03	●	7.5	41	1.4	8	29	36	79	
ME20750S05	●	7.5	53	1.4	8	43	36	91	

※ 請接下頁。 ※ Continued on next page.




新規格上市
New Specification Arrival

產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
		DC	LCF	PL	DCON	LU	LS	OAL	
ME20760S03		7.6	41	1.4	8	29	36	79	
ME20760S05	●	7.6	53	1.4	8	43	36	91	
ME20770S03	●	7.7	41	1.4	8	29	36	79	
ME20770S05	●	7.7	53	1.4	8	43	36	91	
ME20780S03	●	7.8	41	1.4	8	29	36	79	
ME20780S05	●	7.8	53	1.4	8	43	36	91	
ME20790S03	●	7.9	41	1.4	8	29	36	79	
ME20790S05	●	7.9	53	1.4	8	43	36	91	
ME20800S03	●	8	41	1.5	8	29	36	79	
ME20800S05	●	8	53	1.5	8	43	36	91	
ME20810S03	●	8.1	47	1.5	10	35	40	89	
ME20810S05	●	8.1	61	1.5	10	49	40	103	
ME20820S03	●	8.2	47	1.5	10	35	40	89	
ME20820S05	●	8.2	61	1.5	10	49	40	103	
ME20830S03	●	8.3	47	1.5	10	35	40	89	
ME20830S05	●	8.3	61	1.5	10	49	40	103	
ME20840S03	●	8.4	47	1.5	10	35	40	89	
ME20840S05	●	8.4	61	1.5	10	49	40	103	
ME20850S03	●	8.5	47	1.5	10	35	40	89	
ME20850S05	●	8.5	61	1.5	10	49	40	103	
ME20860S03	●	8.6	47	1.6	10	35	40	89	
ME20860S05	●	8.6	61	1.6	10	49	40	103	
ME20870S03	●	8.7	47	1.6	10	35	40	89	
ME20870S05	●	8.7	61	1.6	10	49	40	103	
ME20880S03	●	8.8	47	1.6	10	35	40	89	
ME20880S05	●	8.8	61	1.6	10	49	40	103	
ME20890S03	●	8.9	47	1.6	10	35	40	89	
ME20890S05	●	8.9	61	1.6	10	49	40	103	
ME20900S03	●	9	47	1.6	10	35	40	89	
ME20900S05	●	9	61	1.6	10	49	40	103	
ME20910S03	●	9.1	47	1.7	10	35	40	89	
ME20910S05	●	9.1	61	1.7	10	49	40	103	
ME20920S03	●	9.2	47	1.7	10	35	40	89	

※ 請接下頁。 ※ Continued on next page.

產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
		DC	LCF	PL	DCON	LU	LS	OAL	
ME20920S05	●	9.2	61	1.7	10	49	40	103	
ME20930S03	●	9.3	47	1.7	10	35	40	89	
ME20930S05	●	9.3	61	1.7	10	49	40	103	
ME20940S03	●	9.4	47	1.7	10	35	40	89	
ME20940S05	●	9.4	61	1.7	10	49	40	103	
ME20950S03	●	9.5	47	1.7	10	35	40	89	
ME20950S05	●	9.5	61	1.7	10	49	40	103	
ME20960S03	●	9.6	47	1.7	10	35	40	89	
ME20960S05	●	9.6	61	1.7	10	49	40	103	
ME20970S03	●	9.7	47	1.8	10	35	40	89	
ME20970S05	●	9.7	61	1.8	10	49	40	103	
ME20980S03	●	9.8	47	1.8	10	35	40	89	
ME20980S05	●	9.8	61	1.8	10	49	40	103	
ME20990S03	●	9.9	47	1.8	10	35	40	89	
ME20990S05	●	9.9	61	1.8	10	49	40	103	
ME21000S03	●	10	47	1.8	10	35	40	89	
ME21000S05	●	10	61	1.8	10	49	40	103	
ME21010S03	●	10.1	55	1.8	12	40	45	102	
ME21010S05	●	10.1	71	1.8	12	56	45	118	
ME21020S03	●	10.2	55	1.9	12	40	45	102	
ME21020S05	●	10.2	71	1.9	12	56	45	118	
ME21030S03	●	10.3	55	1.9	12	40	45	102	
ME21030S05	●	10.3	71	1.9	12	56	45	118	
ME21040S03	●	10.4	55	1.9	12	40	45	102	
ME21040S05	●	10.4	71	1.9	12	56	45	118	
ME21050S03	●	10.5	55	1.9	12	40	45	102	
ME21050S05	●	10.5	71	1.9	12	56	45	118	
ME21060S03	●	10.6	55	1.9	12	40	45	102	
ME21060S05	●	10.6	71	1.9	12	56	45	118	
ME21070S03	●	10.7	55	1.9	12	40	45	102	
ME21070S05	●	10.7	71	1.9	12	56	45	118	
ME21080S03	●	10.8	55	2	12	40	45	102	
ME21080S05	●	10.8	71	2	12	56	45	118	
ME21090S03	●	10.9	55	2	12	40	45	102	
ME21090S05	●	10.9	71	2	12	56	45	118	
ME21100S03	●	11	55	2	12	40	45	102	
ME21100S05	●	11	71	2	12	56	45	118	
ME21110S03	●	11.1	55	2	12	40	45	102	
ME21110S05	●	11.1	71	2	12	56	45	118	
ME21120S03	●	11.2	55	2	12	40	45	102	
ME21120S05	●	11.2	71	2	12	56	45	118	
ME21130S03	●	11.3	55	2.1	12	40	45	102	

※ 請接下頁。 ※ Continued on next page.




新規格上市
New Specification Arrival

產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
		DC	LCF	PL	DCON	LU	LS	OAL	
ME21130S05	●	11.3	71	2.1	12	56	45	118	
ME21140S03	●	11.4	55	2.1	12	40	45	102	
ME21140S05	●	11.4	71	2.1	12	56	45	118	
ME21150S03	●	11.5	55	2.1	12	40	45	102	
ME21150S05	●	11.5	71	2.1	12	56	45	118	
ME21160S03		11.6	55	2.1	12	40	45	102	
ME21160S05	●	11.6	71	2.1	12	56	45	118	
ME21170S03	●	11.7	55	2.1	12	40	45	102	
ME21170S05	●	11.7	71	2.1	12	56	45	118	
ME21180S03	●	11.8	55	2.1	12	40	45	102	
ME21180S05	●	11.8	71	2.1	12	56	45	118	
ME21190S03	●	11.9	55	2.2	12	40	45	102	
ME21190S05	●	11.9	71	2.2	12	56	45	118	
ME21200S03	●	12	55	2.2	12	40	45	102	
ME21200S05	●	12	71	2.2	12	56	45	118	
ME21210S03	●	12.1	60	2.2	14	43	45	107	
ME21210S05		12.1	77	2.2	14	60	45	124	
ME21220S03	●	12.2	60	2.2	14	43	45	107	
ME21220S05		12.2	77	2.2	14	60	45	124	
ME21230S03		12.3	60	2.2	14	43	45	107	
ME21230S05		12.3	77	2.2	14	60	45	124	
ME21250S03	●	12.5	60	2.3	14	43	45	107	
ME21250S05	●	12.5	77	2.3	14	60	45	124	
NEW ME21260S05	●	12.6	77	2.3	14	60	45	124	
ME21270S03	●	12.7	60	2.3	14	43	45	107	
ME21270S05		12.7	77	2.3	14	60	45	124	
ME21280S03	●	12.8	60	2.3	14	43	45	107	
ME21280S05		12.8	77	2.3	14	60	45	124	
ME21290S03	●	12.9	60	2.3	14	43	45	107	
ME21290S05		12.9	77	2.3	14	60	45	124	
ME21300S03	●	13	60	2.4	14	43	45	107	
ME21300S05	●	13	77	2.4	14	60	45	124	
ME21310S03	●	13.1	60	2.4	14	43	45	107	

※ 請接下頁。 ※ Continued on next page.

產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
		DC	LCF	PL	DCON	LU	LS	OAL	
ME21310S05		13.1	77	2.4	14	60	45	124	
ME21350S03	●	13.5	60	2.5	14	43	45	107	
ME21350S05	●	13.5	77	2.5	14	60	45	124	
ME21380S03		13.8	60	2.5	14	43	45	107	
ME21380S05		13.8	77	2.5	14	60	45	124	
ME21400S03	●	14	60	2.5	14	43	45	107	
ME21400S05		14	77	2.5	14	60	45	124	
ME21430S03		14.3	65	2.6	16	45	48	115	
ME21430S05		14.3	83	2.6	16	63	48	133	
ME21450S03	●	14.5	65	2.6	16	45	48	115	
ME21450S05	●	14.5	83	2.6	16	63	48	133	
ME21480S03		14.8	65	2.7	16	45	48	115	
ME21480S05		14.8	83	2.7	16	63	48	133	
ME21500S03	●	15	65	2.7	16	45	48	115	
ME21500S05	●	15	83	2.7	16	63	48	133	
ME21510S03		15.1	65	2.7	16	45	48	115	
ME21510S05		15.1	83	2.7	16	63	48	133	
ME21550S03	●	15.5	65	2.8	16	45	48	115	
ME21550S05		15.5	83	2.8	16	63	48	133	
ME21580S03		15.8	65	2.9	16	45	48	115	
ME21580S05		15.8	83	2.9	16	63	48	133	
ME21600S03	●	16	65	2.9	16	45	48	115	
ME21600S05	●	16	83	2.9	16	63	48	133	
ME21650S03		16.5	73	3	18	51	48	123	
ME21650S05		16.5	93	3	18	71	48	143	
ME21680S03		16.8	73	3.1	18	51	48	123	
ME21680S05		16.8	93	3.1	18	71	48	143	
ME21700S03		17	73	3.1	18	51	48	123	
ME21700S05		17	93	3.1	18	71	48	143	
ME21750S03		17.5	73	3.2	18	51	48	123	
ME21750S05		17.5	93	3.2	18	71	48	143	
ME21780S03		17.8	73	3.2	18	51	48	123	
ME21780S05		17.8	93	3.2	18	71	48	143	
ME21790S03		17.9	73	3.3	18	51	48	123	
ME21790S05		17.9	93	3.3	18	71	48	143	
ME21800S03		18	73	3.3	18	51	48	123	
ME21800S05		18	93	3.3	18	71	48	143	
ME21830S03		18.3	79	3.3	20	55	50	131	
ME21830S05		18.3	101	3.3	20	77	50	153	
ME21850S03		18.5	79	3.4	20	55	50	131	
ME21850S05		18.5	101	3.4	20	77	50	153	
ME21880S03		18.8	79	3.4	20	55	50	131	

※ 請接下頁。 ※ Continued on next page.

ME20 鎢鋼鑽頭
Carbide Drill

新規格上市
New Specification Arrival

產品型號 Model No	在庫 Stock	切削直徑 DC	排屑槽長度 LCF	頂端至肩部尺寸差 PL	柄部直徑 DCON	可使用長度 LU	刀柄長度 LS	全長 OAL	價格 Price
ME21880S05		18.8	101	3.4	20	77	50	153	
ME21900S03		19	79	3.5	20	55	50	131	
ME21900S05		19	101	3.5	20	77	50	153	
ME21950S03		19.5	79	3.5	20	55	50	131	
ME21950S05		19.5	101	3.5	20	77	50	153	
ME21980S03		19.8	79	3.6	20	55	50	131	
ME21980S05		19.8	101	3.6	20	77	50	153	
ME22000S03	●	20	79	3.6	20	55	50	131	
ME22000S05	●	20	101	3.6	20	77	50	153	



SPE 20 系列 鎢鋼鑽頭 Carbide Drill

夾角140°設計 140 Angle Design

鑽尖結構優化設計，擁有低抗阻能力

大幅提升切削排屑性能

Drill tip structure design is optimized,
which has low resistance performance.

Which greatly improves cutting
and chip removal performance.



特殊材質 Material

合金鋼
Alloy Steel

碳鋼
Carbon Steel

不鏽鋼
Stainless steel

專用

尺寸齊全 歡迎詢問

Welcome to inquiry, a complete
range of specifications are in stock

全新SP600塗層 New SP600 Coating

高剛性、耐磨耗材質、抗崩損、耐高溫，抗震性絕佳


High rigidity wear resistance, chipping resistance,
high temperature resistance, and excellent earthquake
resistance.

以進口頂級高精密多軸磨刀機研磨生產，尺寸精準且穩定

Grinding and production using imported top-grade high-precision
multi-axis knife grinders, the dimensions are accurate and stable.



SPE20 鎢鋼鑽頭
Carbide Drill



新品上市
New Arrival


	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	SPE20150S05		1.5	12	0.3	4	9	28	58	
NEW	SPE20160S03		1.6	9	0.3	4	6	28	58	
NEW	SPE20180S03	●	1.8	9	0.3	4	6	28	58	
NEW	SPE20200S03		2	13	0.4	4	9	28	58	
NEW	SPE20200S05		2	18	0.4	4	14	28	58	
NEW	SPE20210S03		2.1	13	0.4	4	9	28	58	
NEW	SPE20210S05		2.1	18	0.4	4	14	28	58	
NEW	SPE20220S03		2.2	13	0.4	4	9	28	58	
NEW	SPE20220S05		2.2	18	0.4	4	14	28	58	
NEW	SPE20230S03		2.3	13	0.4	4	9	28	58	
NEW	SPE20230S05		2.3	18	0.4	4	14	28	58	
NEW	SPE20238S03	●	2.38	17	0.4	4	12	28	58	
NEW	SPE20240S03	●	2.4	17	0.4	4	12	28	58	
NEW	SPE20240S05		2.4	22	0.4	4	17	28	58	
NEW	SPE20250S03		2.5	17	0.5	4	12	28	58	
NEW	SPE20250S05		2.5	22	0.5	4	17	28	58	
NEW	SPE20260S03		2.6	17	0.5	4	12	28	58	
NEW	SPE20260S05		2.6	22	0.5	4	17	28	58	
NEW	SPE20270S03		2.7	17	0.5	4	12	28	58	
NEW	SPE20270S05		2.7	22	0.5	4	17	28	58	
NEW	SPE20278S03	●	2.78	17	0.5	4	12	28	58	
NEW	SPE20280S03		2.8	17	0.5	4	12	28	58	
NEW	SPE20280S05		2.8	22	0.5	4	17	28	58	
NEW	SPE20290S03		2.9	17	0.5	4	12	28	58	
NEW	SPE20290S05		2.9	22	0.5	4	17	28	58	
NEW	SPE20300S03D4		3	20	0.5	4	14	36	62	
NEW	SPE20300S03		3	20	0.5	6	14	36	62	
NEW	SPE20300S05D4		3	28	0.5	4	23	36	66	
NEW	SPE20300S05		3	28	0.5	6	23	36	66	
NEW	SPE20310S03D4		3.1	20	0.6	4	14	36	62	
NEW	SPE20310S03		3.1	20	0.6	6	14	36	62	
NEW	SPE20310S05D4		3.1	28	0.6	4	23	36	66	
NEW	SPE20310S05		3.1	28	0.6	6	23	36	66	

※ 請接下頁。 ※ Continued on next page.

	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部 尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	SPE20320S03D4		3.2	20	0.6	4	14	36	62	
NEW	SPE20320S03		3.2	20	0.6	6	14	36	62	
NEW	SPE20320S05D4		3.2	28	0.6	4	23	36	66	
NEW	SPE20320S05		3.2	28	0.6	6	23	36	66	
NEW	SPE20330S03D4		3.3	20	0.6	4	14	36	62	
NEW	SPE20330S03		3.3	20	0.6	6	14	36	62	
NEW	SPE20330S05D4		3.3	28	0.6	4	23	36	66	
NEW	SPE20330S05		3.3	28	0.6	6	23	36	66	
NEW	SPE20340S03D4		3.4	20	0.6	4	14	36	62	
NEW	SPE20340S03		3.4	20	0.6	6	14	36	62	
NEW	SPE20340S05D4		3.4	28	0.6	4	23	36	66	
NEW	SPE20340S05		3.4	28	0.6	6	23	36	66	
NEW	SPE20350S03D4		3.5	20	0.6	4	14	36	62	
NEW	SPE20350S03		3.5	20	0.6	6	14	36	62	
NEW	SPE20350S05D4		3.5	28	0.6	4	23	36	66	
NEW	SPE20350S05		3.5	28	0.6	6	23	36	66	
NEW	SPE20360S03D4		3.6	20	0.7	4	14	36	62	
NEW	SPE20360S03		3.6	20	0.7	6	14	36	62	
NEW	SPE20360S05D4		3.6	28	0.7	4	23	36	66	
NEW	SPE20360S05		3.6	28	0.7	6	23	36	66	
NEW	SPE20368S03	●	3.68	20	0.7	6	14	36	62	
NEW	SPE20370S03D4		3.7	20	0.7	4	14	36	62	
NEW	SPE20370S03	●	3.7	20	0.7	6	14	36	62	
NEW	SPE20370S05D4		3.7	28	0.7	4	23	36	66	
NEW	SPE20370S05		3.7	28	0.7	6	23	36	66	
NEW	SPE20380S03D4		3.8	24	0.7	4	17	36	66	
NEW	SPE20380S03		3.8	24	0.7	6	17	36	66	
NEW	SPE20380S05D4		3.8	36	0.7	4	29	36	74	
NEW	SPE20380S05		3.8	36	0.7	6	29	36	74	
NEW	SPE20390S03D4		3.9	24	0.7	4	17	36	66	
NEW	SPE20390S03		3.9	24	0.7	6	17	36	66	
NEW	SPE20390S05D4		3.9	36	0.7	4	29	36	74	
NEW	SPE20390S05		3.9	36	0.7	6	29	36	74	
NEW	SPE20400S03D4		4	24	0.7	4	17	36	66	
NEW	SPE20400S03		4	24	0.7	6	17	36	66	
NEW	SPE20400S05D4		4	36	0.7	4	29	36	74	
NEW	SPE20400S05		4	36	0.7	6	29	36	74	
NEW	SPE20410S03		4.1	24	0.7	6	17	36	66	
NEW	SPE20410S05		4.1	36	0.7	6	29	36	74	
NEW	SPE20420S03		4.2	24	0.8	6	17	36	66	
NEW	SPE20420S05		4.2	36	0.8	6	29	36	74	
NEW	SPE20430S03		4.3	24	0.8	6	17	36	66	

※ 請接下頁。 ※ Continued on next page.

SPE20 鎢鋼鑽頭
Carbide Drill



新品上市
New Arrival


產品型號 Model No	在庫 Stock	切削直徑 DC	排屑槽長度 LCF	頂端至肩部尺寸差 PL	柄部直徑 DCON	可使用長度 LU	刀柄長度 LS	全長 OAL	價格 Price
NEW SPE20430S05		4.3	36	0.8	6	29	36	74	
NEW SPE20440S03		4.4	24	0.8	6	17	36	66	
NEW SPE20440S05		4.4	36	0.8	6	29	36	74	
NEW SPE20450S03		4.5	24	0.8	6	17	36	66	
NEW SPE20450S05	●	4.5	36	0.8	6	29	36	74	
NEW SPE20460S03		4.6	24	0.8	6	17	36	66	
NEW SPE20460S05		4.6	36	0.8	6	29	36	74	
NEW SPE20465S03	●	4.65	24	0.9	6	17	36	66	
NEW SPE20470S03		4.7	24	0.9	6	17	36	66	
NEW SPE20470S05		4.7	36	0.9	6	29	36	74	
NEW SPE20480S03		4.8	28	0.9	6	20	36	66	
NEW SPE20480S05		4.8	44	0.9	6	35	36	82	
NEW SPE20490S03		4.9	28	0.9	6	20	36	66	
NEW SPE20490S05		4.9	44	0.9	6	35	36	82	
NEW SPE20500S03		5	28	0.9	6	20	36	66	
NEW SPE20500S05		5	44	0.9	6	35	36	82	
NEW SPE20510S03		5.1	28	0.9	6	20	36	66	
NEW SPE20510S05		5.1	44	0.9	6	35	36	82	
NEW SPE20520S03		5.2	28	0.9	6	20	36	66	
NEW SPE20520S05		5.2	44	0.9	6	35	36	82	
NEW SPE20530S03		5.3	28	1	6	20	36	66	
NEW SPE20530S05		5.3	44	1	6	35	36	82	
NEW SPE20540S03		5.4	28	1	6	20	36	66	
NEW SPE20540S05		5.4	44	1	6	35	36	82	
NEW SPE20550S03		5.5	28	1	6	20	36	66	
NEW SPE20550S05		5.5	44	1	6	35	36	82	
NEW SPE20560S03		5.6	28	1	6	20	36	66	
NEW SPE20560S05		5.6	44	1	6	35	36	82	
NEW SPE20570S03		5.7	28	1	6	20	36	66	
NEW SPE20570S05		5.7	44	1	6	35	36	82	
NEW SPE20580S03		5.8	28	1.1	6	20	36	66	
NEW SPE20580S05		5.8	44	1.1	6	35	36	82	
NEW SPE20590S03		5.9	28	1.1	6	20	36	66	

※ 請接下頁。 ※ Continued on next page.

	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	SPE20590S05		5.9	44	1.1	6	35	36	82	
NEW	SPE20600S03		6	28	1.1	6	20	36	66	
NEW	SPE20600S05		6	44	1.1	6	35	36	82	
NEW	SPE20610S03		6.1	34	1.1	8	24	36	79	
NEW	SPE20610S05		6.1	53	1.1	8	43	36	91	
NEW	SPE20620S03		6.2	34	1.1	8	24	36	79	
NEW	SPE20620S05		6.2	53	1.1	8	43	36	91	
NEW	SPE20630S03		6.3	34	1.1	8	24	36	79	
NEW	SPE20630S05		6.3	53	1.1	8	43	36	91	
NEW	SPE20640S03		6.4	34	1.2	8	24	36	79	
NEW	SPE20640S05		6.4	53	1.2	8	43	36	91	
NEW	SPE20650S03		6.5	34	1.2	8	24	36	79	
NEW	SPE20650S05		6.5	53	1.2	8	43	36	91	
NEW	SPE20660S03		6.6	34	1.2	8	24	36	79	
NEW	SPE20660S05		6.6	53	1.2	8	43	36	91	
NEW	SPE20670S03		6.7	34	1.2	8	24	36	79	
NEW	SPE20670S05		6.7	53	1.2	8	43	36	91	
NEW	SPE20680S03		6.8	34	1.2	8	24	36	79	
NEW	SPE20680S05		6.8	53	1.2	8	43	36	91	
NEW	SPE20690S03		6.9	34	1.3	8	24	36	79	
NEW	SPE20690S05		6.9	53	1.3	8	43	36	91	
NEW	SPE20700S03		7	34	1.3	8	24	36	79	
NEW	SPE20700S05		7	53	1.3	8	43	36	91	
NEW	SPE20710S03		7.1	41	1.3	8	29	36	79	
NEW	SPE20710S05		7.1	53	1.3	8	43	36	91	
NEW	SPE20720S03		7.2	41	1.3	8	29	36	79	
NEW	SPE20720S05		7.2	53	1.3	8	43	36	91	
NEW	SPE20730S03		7.3	41	1.3	8	29	36	79	
NEW	SPE20730S05		7.3	53	1.3	8	43	36	91	
NEW	SPE20740S03		7.4	41	1.3	8	29	36	79	
NEW	SPE20740S05		7.4	53	1.3	8	43	36	91	
NEW	SPE20750S03		7.5	41	1.4	8	29	36	79	
NEW	SPE20750S05		7.5	53	1.4	8	43	36	91	
NEW	SPE20760S03		7.6	41	1.4	8	29	36	79	
NEW	SPE20760S05		7.6	53	1.4	8	43	36	91	
NEW	SPE20770S03		7.7	41	1.4	8	29	36	79	
NEW	SPE20770S05		7.7	53	1.4	8	43	36	91	
NEW	SPE20780S03		7.8	41	1.4	8	29	36	79	
NEW	SPE20780S05		7.8	53	1.4	8	43	36	91	
NEW	SPE20790S03		7.9	41	1.4	8	29	36	79	
NEW	SPE20790S05		7.9	53	1.4	8	43	36	91	
NEW	SPE20800S03		8	41	1.5	8	29	36	79	

※ 請接下一頁。 ※ Continued on next page.

SPE20 鎢鋼鑽頭
Carbide Drill




新品上市
New Arrival

	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	SPE20800S05		8	53	1.5	8	43	36	91	
NEW	SPE20810S03		8.1	47	1.5	10	35	40	89	
NEW	SPE20810S05		8.1	61	1.5	10	49	40	103	
NEW	SPE20820S03		8.2	47	1.5	10	35	40	89	
NEW	SPE20820S05		8.2	61	1.5	10	49	40	103	
NEW	SPE20830S03		8.3	47	1.5	10	35	40	89	
NEW	SPE20830S05		8.3	61	1.5	10	49	40	103	
NEW	SPE20840S03		8.4	47	1.5	10	35	40	89	
NEW	SPE20840S05		8.4	61	1.5	10	49	40	103	
NEW	SPE20850S03		8.5	47	1.5	10	35	40	89	
NEW	SPE20850S05		8.5	61	1.5	10	49	40	103	
NEW	SPE20860S03		8.6	47	1.6	10	35	40	89	
NEW	SPE20860S05		8.6	61	1.6	10	49	40	103	
NEW	SPE20870S03		8.7	47	1.6	10	35	40	89	
NEW	SPE20870S05		8.7	61	1.6	10	49	40	103	
NEW	SPE20880S03		8.8	47	1.6	10	35	40	89	
NEW	SPE20880S05		8.8	61	1.6	10	49	40	103	
NEW	SPE20890S03		8.9	47	1.6	10	35	40	89	
NEW	SPE20890S05		8.9	61	1.6	10	49	40	103	
NEW	SPE20900S03		9	47	1.6	10	35	40	89	
NEW	SPE20900S05		9	61	1.6	10	49	40	103	
NEW	SPE20910S03		9.1	47	1.7	10	35	40	89	
NEW	SPE20910S05		9.1	61	1.7	10	49	40	103	
NEW	SPE20920S03		9.2	47	1.7	10	35	40	89	
NEW	SPE20920S05		9.2	61	1.7	10	49	40	103	
NEW	SPE20930S03		9.3	47	1.7	10	35	40	89	
NEW	SPE20930S05		9.3	61	1.7	10	49	40	103	
NEW	SPE20940S03		9.4	47	1.7	10	35	40	89	
NEW	SPE20940S05		9.4	61	1.7	10	49	40	103	
NEW	SPE20950S03		9.5	47	1.7	10	35	40	89	
NEW	SPE20950S05		9.5	61	1.7	10	49	40	103	
NEW	SPE20960S03		9.6	47	1.7	10	35	40	89	
NEW	SPE20960S05		9.6	61	1.7	10	49	40	103	

※ 請接下頁。 ※ Continued on next page.

	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部 尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	SPE20970S03		9.7	61	1.8	10	35	40	89	
NEW	SPE20970S05		9.7	61	1.8	10	49	40	103	
NEW	SPE20980S03		9.8	47	1.8	10	35	40	89	
NEW	SPE20980S05		9.8	61	1.8	10	49	40	103	
NEW	SPE20990S03		9.9	47	1.8	10	35	40	89	
NEW	SPE20990S05		9.9	61	1.8	10	49	40	103	
NEW	SPE21000S03		10	47	1.8	10	35	40	89	
NEW	SPE21000S05		10	61	1.8	10	49	40	103	
NEW	SPE21010S03		10.1	55	1.8	12	40	45	102	
NEW	SPE21010S05		10.1	71	1.8	12	56	45	118	
NEW	SPE21020S03		10.2	55	1.9	12	40	45	102	
NEW	SPE21020S05		10.2	71	1.9	12	56	45	118	
NEW	SPE21030S03		10.3	55	1.9	12	40	45	102	
NEW	SPE21030S05		10.3	71	1.9	12	56	45	118	
NEW	SPE21040S03		10.4	55	1.9	12	40	45	102	
NEW	SPE21040S05		10.4	71	1.9	12	56	45	118	
NEW	SPE21050S03		10.5	55	1.9	12	40	45	102	
NEW	SPE21050S05		10.5	71	1.9	12	56	45	118	
NEW	SPE21060S03		10.6	55	1.9	12	40	45	102	
NEW	SPE21060S05		10.6	71	1.9	12	56	45	118	
NEW	SPE21070S03		10.7	55	1.9	12	40	45	102	
NEW	SPE21070S05		10.7	71	1.9	12	56	45	118	
NEW	SPE21080S03		10.8	55	2	12	40	45	102	
NEW	SPE21080S05		10.8	71	2	12	56	45	118	
NEW	SPE21090S03		10.9	55	2	12	40	45	102	
NEW	SPE21090S05		10.9	71	2	12	56	45	118	
NEW	SPE21100S03		11	55	2	12	40	45	102	
NEW	SPE21100S05		11	71	2	12	56	45	118	
NEW	SPE21110S03		11.1	55	2	12	40	45	102	
NEW	SPE21110S05		11.1	71	2	12	56	45	118	
NEW	SPE21120S03		11.2	55	2	12	40	45	102	
NEW	SPE21120S05		11.2	71	2	12	56	45	118	
NEW	SPE21130S03		11.3	55	2.1	12	40	45	102	
NEW	SPE21130S05		11.3	71	2.1	12	56	45	118	
NEW	SPE21140S03		11.4	55	2.1	12	40	45	102	
NEW	SPE21140S05		11.4	71	2.1	12	56	45	118	
NEW	SPE21150S03		11.5	55	2.1	12	40	45	102	
NEW	SPE21150S05		11.5	71	2.1	12	56	45	118	
NEW	SPE21160S03		11.6	55	2.1	12	40	45	102	
NEW	SPE21160S05		11.6	71	2.1	12	56	45	118	
NEW	SPE21170S03		11.7	55	2.1	12	40	45	102	
NEW	SPE21170S05		11.7	71	2.1	12	56	45	118	

※ 請接下頁。 ※ Continued on next page.



新品上市
New Arrival

產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部 尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
		DC	LCF	PL	DCON	LU	LS	OAL	
NEW SPE21180S03		11.8	55	2.1	12	40	45	102	
NEW SPE21180S05		11.8	71	2.1	12	56	45	118	
NEW SPE21190S03		11.9	55	2.2	12	40	45	102	
NEW SPE21190S05		11.9	71	2.2	12	56	45	118	
NEW SPE21200S03		12	55	2.2	12	40	45	102	
NEW SPE21200S05		12	71	2.2	12	56	45	118	



夾角140°設計 140 Angle Design

鑽尖結構優化設計，擁有低抗阻能力
高進給出水設計，大幅提升切削排屑性能

Drill tip structure design is optimized, which has low resistance performance. High feed coolant design, which greatly improves cutting and chip removal performance.



SPEC 20系列

中心出水設計 鎢鋼鑽頭 Carbide Drill With Coolant

中心出水設計 使鑽孔加工表現穩定
且延長加工使用時間

The central water outlet design

Ensures stable drilling performance and extends the processing time.

全新SP600塗層 高剛性、耐磨耗材質
抗崩損、耐高溫，抗震性絕佳

New SP600 Coating

High rigidity wear resistance, chipping resistance, high temperature resistance, and excellent earthquake resistance.

以進口頂級高精密多軸磨刀機研磨生產
尺寸精準且穩定

Grinding and production using imported top-grade high-precision multi-axis knife grinders, the dimensions are accurate and stable.

特殊材質 Material

合金鋼
Alloy Steel

碳鋼
Carbon Steel

不鏽鋼
Stainless steel


專用



尺寸齊全 歡迎詢問

Welcome to inquiry, a complete range of specifications are in stock

SPEC20 中心出水鎢鋼鑽頭
Carbide Drill With Coolant



新品上市
New Arrival


產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部 尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
		DC	LCF	PL	DCON	LU	LS	OAL	
NEW SPEC20150S05		1.5	12	0.3	4	9	28	58	
NEW SPEC20160S03		1.6	9	0.3	4	6	28	58	
NEW SPEC20180S03		1.8	9	0.3	4	6	28	58	
NEW SPEC20200S03		2	13	0.4	4	9	28	58	
NEW SPEC20200S05		2	18	0.4	4	14	28	58	
NEW SPEC20210S03		2.1	13	0.4	4	9	28	58	
NEW SPEC20210S05		2.1	18	0.4	4	14	28	58	
NEW SPEC20220S03		2.2	13	0.4	4	9	28	58	
NEW SPEC20220S05		2.2	18	0.4	4	14	28	58	
NEW SPEC20230S03		2.3	13	0.4	4	9	28	58	
NEW SPEC20230S05		2.3	18	0.4	4	14	28	58	
NEW SPEC20240S03		2.4	17	0.4	4	12	28	58	
NEW SPEC20240S05		2.4	22	0.4	4	17	28	58	
NEW SPEC20250S03		2.5	17	0.5	4	12	28	58	
NEW SPEC20250S05		2.5	22	0.5	4	17	28	58	
NEW SPEC20260S03		2.6	17	0.5	4	12	28	58	
NEW SPEC20260S05		2.6	22	0.5	4	17	28	58	
NEW SPEC20270S03		2.7	17	0.5	4	12	28	58	
NEW SPEC20270S05		2.7	22	0.5	4	17	28	58	
NEW SPEC20280S03		2.8	17	0.5	4	12	28	58	
NEW SPEC20280S05		2.8	22	0.5	4	17	28	58	
NEW SPEC20290S03		2.9	17	0.5	4	12	28	58	
NEW SPEC20290S05		2.9	22	0.5	4	17	28	58	
NEW SPEC20300S03D4		3	20	0.5	4	14	36	62	
NEW SPEC20300S03		3	20	0.5	6	14	36	62	
NEW SPEC20300S05D4		3	28	0.5	4	23	36	66	
NEW SPEC20300S05		3	28	0.5	6	23	36	66	
NEW SPEC20310S03D4		3.1	20	0.6	4	14	36	62	
NEW SPEC20310S03	●	3.1	20	0.6	6	14	36	62	
NEW SPEC20310S05D4		3.1	28	0.6	4	23	36	66	
NEW SPEC20310S05		3.1	28	0.6	6	23	36	66	
NEW SPEC20320S03D4		3.2	20	0.6	4	14	36	62	
NEW SPEC20320S03		3.2	20	0.6	6	14	36	62	

※ 請接下頁。 ※ Continued on next page.

	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部 尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	SPEC20320S05D4		3.2	28	0.6	4	23	36	66	
NEW	SPEC20320S05		3.2	28	0.6	6	23	36	66	
NEW	SPEC20330S03D4		3.3	20	0.6	4	14	36	62	
NEW	SPEC20330S03		3.3	20	0.6	6	14	36	62	
NEW	SPEC20330S05D4		3.3	28	0.6	4	23	36	66	
NEW	SPEC20330S05		3.3	28	0.6	6	23	36	66	
NEW	SPEC20340S03D4		3.4	20	0.6	4	14	36	62	
NEW	SPEC20340S03		3.4	20	0.6	6	14	36	62	
NEW	SPEC20340S05D4		3.4	28	0.6	4	23	36	66	
NEW	SPEC20340S05		3.4	28	0.6	6	23	36	66	
NEW	SPEC20350S03D4		3.5	20	0.6	4	14	36	62	
NEW	SPEC20350S03		3.5	20	0.6	6	14	36	62	
NEW	SPEC20350S05D4		3.5	28	0.6	4	23	36	66	
NEW	SPEC20350S05		3.5	28	0.6	6	23	36	66	
NEW	SPEC20360S03D4		3.6	20	0.7	4	14	36	62	
NEW	SPEC20360S03		3.6	20	0.7	6	14	36	62	
NEW	SPEC20360S05D4		3.6	28	0.7	4	23	36	66	
NEW	SPEC20360S05		3.6	28	0.7	6	23	36	66	
NEW	SPEC20370S03D4		3.7	20	0.7	4	14	36	62	
NEW	SPEC20370S03		3.7	20	0.7	6	14	36	62	
NEW	SPEC20370S05D4		3.7	28	0.7	4	23	36	66	
NEW	SPEC20370S05		3.7	28	0.7	6	23	36	66	
NEW	SPEC20380S03D4		3.8	24	0.7	4	17	36	66	
NEW	SPEC20380S03		3.8	24	0.7	6	17	36	66	
NEW	SPEC20380S05D4		3.8	36	0.7	4	29	36	74	
NEW	SPEC20380S05		3.8	36	0.7	6	29	36	74	
NEW	SPEC20390S03D4		3.9	24	0.7	4	17	36	66	
NEW	SPEC20390S03		3.9	24	0.7	6	17	36	66	
NEW	SPEC20390S05D4		3.9	36	0.7	4	29	36	74	
NEW	SPEC20390S05		3.9	36	0.7	6	29	36	74	
NEW	SPEC20400S03D4		4	24	0.7	4	17	36	66	
NEW	SPEC20400S03		4	24	0.7	6	17	36	66	
NEW	SPEC20400S05D4		4	36	0.7	4	29	36	74	
NEW	SPEC20400S05		4	36	0.7	6	29	36	74	
NEW	SPEC20410S03		4.1	24	0.7	6	17	36	66	
NEW	SPEC20410S05		4.1	36	0.7	6	29	36	74	
NEW	SPEC20420S03		4.2	24	0.8	6	17	36	66	
NEW	SPEC20420S05		4.2	36	0.8	6	29	36	74	
NEW	SPEC20430S03		4.3	24	0.8	6	17	36	66	
NEW	SPEC20430S05	●	4.3	36	0.8	6	29	36	74	
NEW	SPEC20440S03		4.4	24	0.8	6	17	36	66	
NEW	SPEC20440S05		4.4	36	0.8	6	29	36	74	

※ 請接下頁。 ※ Continued on next page.

SPEC20 中心出水鑄鋼鑽頭
Carbide Drill With Coolant



新品上市
New Arrival


產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部 尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
		DC	LCF	PL	DCON	LU	LS	OAL	
NEW SPEC20450S03		4.5	24	0.8	6	17	36	66	
NEW SPEC20450S05		4.5	36	0.8	6	29	36	74	
NEW SPEC20460S03		4.6	24	0.8	6	17	36	66	
NEW SPEC20460S05		4.6	36	0.8	6	29	36	74	
NEW SPEC20470S03		4.7	24	0.9	6	17	36	66	
NEW SPEC20470S05		4.7	36	0.9	6	29	36	74	
NEW SPEC20480S03		4.8	28	0.9	6	20	36	66	
NEW SPEC20480S05		4.8	44	0.9	6	35	36	82	
NEW SPEC20490S03		4.9	28	0.9	6	20	36	66	
NEW SPEC20490S05		4.9	44	0.9	6	35	36	82	
NEW SPEC20500S03		5	28	0.9	6	20	36	66	
NEW SPEC20500S05		5	44	0.9	6	35	36	82	
NEW SPEC20510S03		5.1	28	0.9	6	20	36	66	
NEW SPEC20510S05	●	5.1	44	0.9	6	35	36	82	
NEW SPEC20520S03		5.2	28	0.9	6	20	36	66	
NEW SPEC20520S05		5.2	44	0.9	6	35	36	82	
NEW SPEC20530S03		5.3	28	1	6	20	36	66	
NEW SPEC20530S05		5.3	44	1	6	35	36	82	
NEW SPEC20540S03		5.4	28	1	6	20	36	66	
NEW SPEC20540S05		5.4	44	1	6	35	36	82	
NEW SPEC20550S03		5.5	28	1	6	20	36	66	
NEW SPEC20550S05		5.5	44	1	6	35	36	82	
NEW SPEC20560S03		5.6	28	1	6	20	36	66	
NEW SPEC20560S05		5.6	44	1	6	35	36	82	
NEW SPEC20570S03		5.7	28	1	6	20	36	66	
NEW SPEC20570S05		5.7	44	1	6	35	36	82	
NEW SPEC20580S03		5.8	28	1.1	6	20	36	66	
NEW SPEC20580S05		5.8	44	1.1	6	35	36	82	
NEW SPEC20590S03		5.9	28	1.1	6	20	36	66	
NEW SPEC20590S05		5.9	44	1.1	6	35	36	82	
NEW SPEC20600S03		6	28	1.1	6	20	36	66	
NEW SPEC20600S05		6	44	1.1	6	35	36	82	
NEW SPEC20610S03		6.1	34	1.1	8	24	36	79	

※ 請接下頁。 ※ Continued on next page.

	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	SPEC20610S05		6.1	53	1.1	8	43	36	91	
NEW	SPEC20620S03		6.2	34	1.1	8	24	36	79	
NEW	SPEC20620S05		6.2	53	1.1	8	43	36	91	
NEW	SPEC20630S03		6.3	34	1.1	8	24	36	79	
NEW	SPEC20630S05		6.3	53	1.1	8	43	36	91	
NEW	SPEC20640S03		6.4	34	1.2	8	24	36	79	
NEW	SPEC20640S05		6.4	53	1.2	8	43	36	91	
NEW	SPEC20650S03		6.5	34	1.2	8	24	36	79	
NEW	SPEC20650S05		6.5	53	1.2	8	43	36	91	
NEW	SPEC20660S03		6.6	34	1.2	8	24	36	79	
NEW	SPEC20660S05		6.6	53	1.2	8	43	36	91	
NEW	SPEC20670S03		6.7	34	1.2	8	24	36	79	
NEW	SPEC20670S05		6.7	53	1.2	8	43	36	91	
NEW	SPEC20680S03		6.8	34	1.2	8	24	36	79	
NEW	SPEC20680S05		6.8	53	1.2	8	43	36	91	
NEW	SPEC20690S03	●	6.9	34	1.3	8	24	36	79	
NEW	SPEC20690S05	●	6.9	53	1.3	8	43	36	91	
NEW	SPEC20700S03		7	34	1.3	8	24	36	79	
NEW	SPEC20700S05		7	53	1.3	8	43	36	91	
NEW	SPEC20710S03		7.1	41	1.3	8	29	36	79	
NEW	SPEC20710S05		7.1	53	1.3	8	43	36	91	
NEW	SPEC20720S03		7.2	41	1.3	8	29	36	79	
NEW	SPEC20720S05		7.2	53	1.3	8	43	36	91	
NEW	SPEC20730S03		7.3	41	1.3	8	29	36	79	
NEW	SPEC20730S05		7.3	53	1.3	8	43	36	91	
NEW	SPEC20740S03		7.4	41	1.3	8	29	36	79	
NEW	SPEC20740S05		7.4	53	1.3	8	43	36	91	
NEW	SPEC20750S03		7.5	41	1.4	8	29	36	79	
NEW	SPEC20750S05		7.5	53	1.4	8	43	36	91	
NEW	SPEC20760S03		7.6	41	1.4	8	29	36	79	
NEW	SPEC20760S05		7.6	53	1.4	8	43	36	91	
NEW	SPEC20770S03		7.7	41	1.4	8	29	36	79	
NEW	SPEC20770S05		7.7	53	1.4	8	43	36	91	
NEW	SPEC20780S03		7.8	41	1.4	8	29	36	79	
NEW	SPEC20780S05		7.8	53	1.4	8	43	36	91	
NEW	SPEC20790S03		7.9	41	1.4	8	29	36	79	
NEW	SPEC20790S05		7.9	53	1.4	8	43	36	91	
NEW	SPEC20800S03		8	41	1.5	8	29	36	79	
NEW	SPEC20800S05	●	8	53	1.5	8	43	36	91	
NEW	SPEC20810S03		8.1	47	1.5	10	35	40	89	
NEW	SPEC20810S05		8.1	61	1.5	10	49	40	103	
NEW	SPEC20820S03		8.2	47	1.5	10	35	40	89	

※ 請接下頁。 ※ Continued on next page.

SPEC20 中心出水鑄鋼鑽頭
Carbide Drill With Coolant



新品上市
New Arrival


	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部 尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	SPEC20820S05		8.2	61	1.5	10	49	40	103	
NEW	SPEC20830S03		8.3	47	1.5	10	35	40	89	
NEW	SPEC20830S05		8.3	61	1.5	10	49	40	103	
NEW	SPEC20840S03		8.4	47	1.5	10	35	40	89	
NEW	SPEC20840S05		8.4	61	1.5	10	49	40	103	
NEW	SPEC20850S03		8.5	47	1.5	10	35	40	89	
NEW	SPEC20850S05		8.5	61	1.5	10	49	40	103	
NEW	SPEC20860S03		8.6	47	1.6	10	35	40	89	
NEW	SPEC20860S05	●	8.6	61	1.6	10	49	40	103	
NEW	SPEC20870S03		8.7	47	1.6	10	35	40	89	
NEW	SPEC20870S05		8.7	61	1.6	10	49	40	103	
NEW	SPEC20880S03		8.8	47	1.6	10	35	40	89	
NEW	SPEC20880S05		8.8	61	1.6	10	49	40	103	
NEW	SPEC20890S03		8.9	47	1.6	10	35	40	89	
NEW	SPEC20890S05		8.9	61	1.6	10	49	40	103	
NEW	SPEC20900S03		9	47	1.6	10	35	40	89	
NEW	SPEC20900S05		9	61	1.6	10	49	40	103	
NEW	SPEC20910S03		9.1	47	1.7	10	35	40	89	
NEW	SPEC20910S05		9.1	61	1.7	10	49	40	103	
NEW	SPEC20920S03		9.2	47	1.7	10	35	40	89	
NEW	SPEC20920S05		9.2	61	1.7	10	49	40	103	
NEW	SPEC20930S03		9.3	47	1.7	10	35	40	89	
NEW	SPEC20930S05		9.3	61	1.7	10	49	40	103	
NEW	SPEC20940S03		9.4	47	1.7	10	35	40	89	
NEW	SPEC20940S05		9.4	61	1.7	10	49	40	103	
NEW	SPEC20950S03		9.5	47	1.7	10	35	40	89	
NEW	SPEC20950S05		9.5	61	1.7	10	49	40	103	
NEW	SPEC20960S03		9.6	47	1.7	10	35	40	89	
NEW	SPEC20960S05		9.6	61	1.7	10	49	40	103	
NEW	SPEC20970S03	●	9.7	61	1.8	10	35	40	89	
NEW	SPEC20970S05		9.7	61	1.8	10	49	40	103	
NEW	SPEC20980S03		9.8	47	1.8	10	35	40	89	
NEW	SPEC20980S05		9.8	61	1.8	10	49	40	103	

※ 請接下頁。 ※ Continued on next page.

	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至屑部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	SPEC20990S03		9.9	47	1.8	10	35	40	89	
NEW	SPEC20990S05		9.9	61	1.8	10	49	40	103	
NEW	SPEC21000S03		10	47	1.8	10	35	40	89	
NEW	SPEC21000S05		10	61	1.8	10	49	40	103	
NEW	SPEC21010S03		10.1	55	1.8	12	40	45	102	
NEW	SPEC21010S05		10.1	71	1.8	12	56	45	118	
NEW	SPEC21020S03		10.2	55	1.9	12	40	45	102	
NEW	SPEC21020S05	●	10.2	71	1.9	12	56	45	118	
NEW	SPEC21030S03		10.3	55	1.9	12	40	45	102	
NEW	SPEC21030S05		10.3	71	1.9	12	56	45	118	
NEW	SPEC21040S03		10.4	55	1.9	12	40	45	102	
NEW	SPEC21040S05		10.4	71	1.9	12	56	45	118	
NEW	SPEC21050S03		10.5	55	1.9	12	40	45	102	
NEW	SPEC21050S05		10.5	71	1.9	12	56	45	118	
NEW	SPEC21060S03		10.6	55	1.9	12	40	45	102	
NEW	SPEC21060S05		10.6	71	1.9	12	56	45	118	
NEW	SPEC21070S03		10.7	55	1.9	12	40	45	102	
NEW	SPEC21070S05		10.7	71	1.9	12	56	45	118	
NEW	SPEC21080S03		10.8	55	2	12	40	45	102	
NEW	SPEC21080S05		10.8	71	2	12	56	45	118	
NEW	SPEC21090S03		10.9	55	2	12	40	45	102	
NEW	SPEC21090S05		10.9	71	2	12	56	45	118	
NEW	SPEC21100S03		11	55	2	12	40	45	102	
NEW	SPEC21100S05		11	71	2	12	56	45	118	
NEW	SPEC21110S03		11.1	55	2	12	40	45	102	
NEW	SPEC21110S05		11.1	71	2	12	56	45	118	
NEW	SPEC21120S03		11.2	55	2	12	40	45	102	
NEW	SPEC21120S05		11.2	71	2	12	56	45	118	
NEW	SPEC21130S03		11.3	55	2.1	12	40	45	102	
NEW	SPEC21130S05		11.3	71	2.1	12	56	45	118	
NEW	SPEC21140S03		11.4	55	2.1	12	40	45	102	
NEW	SPEC21140S05		11.4	71	2.1	12	56	45	118	
NEW	SPEC21150S03		11.5	55	2.1	12	40	45	102	
NEW	SPEC21150S05		11.5	71	2.1	12	56	45	118	
NEW	SPEC21160S03		11.6	55	2.1	12	40	45	102	
NEW	SPEC21160S05		11.6	71	2.1	12	56	45	118	
NEW	SPEC21170S03		11.7	55	2.1	12	40	45	102	
NEW	SPEC21170S05		11.7	71	2.1	12	56	45	118	
NEW	SPEC21180S03		11.8	55	2.1	12	40	45	102	
NEW	SPEC21180S05		11.8	71	2.1	12	56	45	118	
NEW	SPEC21190S03		11.9	55	2.2	12	40	45	102	
NEW	SPEC21190S05		11.9	71	2.2	12	56	45	118	

※ 請接下一頁。 ※ Continued on next page.

SPEC20 中心出水鎢鋼鑽頭
Carbide Drill With Coolant



新品上市
New Arrival

	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	SPEC21200S03		12	55	2.2	12	40	45	102	
NEW	SPEC21200S05		12	71	2.2	12	56	45	118	
NEW	SPEC21210S03		12.1	60	2.2	14	43	45	107	
NEW	SPEC21210S05		12.1	77	2.2	14	60	45	124	
NEW	SPEC21220S03		12.2	60	2.2	14	43	45	107	
NEW	SPEC21220S05		12.2	77	2.2	14	60	45	124	
NEW	SPEC21230S03		12.3	60	2.2	14	43	45	107	
NEW	SPEC21230S05	●	12.3	77	2.2	14	60	45	124	
NEW	SPEC21250S03		12.5	60	2.3	14	43	45	107	
NEW	SPEC21250S05		12.5	77	2.3	14	60	45	124	
NEW	SPEC21260S03		12.6	60	2.3	14	43	45	107	
NEW	SPEC21260S05		12.6	77	2.3	14	60	45	124	
NEW	SPEC21270S03		12.7	60	2.3	14	43	45	107	
NEW	SPEC21270S05		12.7	77	2.3	14	60	45	124	
NEW	SPEC21280S03		12.8	60	2.3	14	43	45	107	
NEW	SPEC21280S05		12.8	77	2.3	14	60	45	124	
NEW	SPEC21290S03		12.9	60	2.3	14	43	45	107	
NEW	SPEC21290S05		12.9	77	2.3	14	60	45	124	
NEW	SPEC21300S03		13	60	2.4	14	43	45	107	
NEW	SPEC21300S05		13	77	2.4	14	60	45	124	
NEW	SPEC21310S03		13.1	60	2.4	14	43	45	107	
NEW	SPEC21310S05		13.1	77	2.4	14	60	45	124	
NEW	SPEC21350S03		13.5	60	2.5	14	43	45	107	
NEW	SPEC21350S05		13.5	77	2.5	14	60	45	124	
NEW	SPEC21380S03		13.8	60	2.5	14	43	45	107	
NEW	SPEC21380S05		13.8	77	2.5	14	60	45	124	
NEW	SPEC21400S03		14	60	2.5	14	43	45	107	
NEW	SPEC21400S05		14	77	2.5	14	60	45	124	
NEW	SPEC21430S03		14.3	65	2.6	16	45	48	115	
NEW	SPEC21430S05		14.3	83	2.6	16	63	48	133	
NEW	SPEC21450S03		14.5	65	2.6	16	45	48	115	
NEW	SPEC21450S05		14.5	83	2.6	16	63	48	133	
NEW	SPEC21480S03		14.8	65	2.7	16	45	48	115	

※ 請接下一页。 ※ Continued on next page.

	產品型號 Model No	在庫 Stock	切削直徑	排屑槽長度	頂端至肩部尺寸差	柄部直徑	可使用長度	刀柄長度	全長	價格 Price
			DC	LCF	PL	DCON	LU	LS	OAL	
NEW	SPEC21480S05		14.8	83	2.7	16	63	48	133	
NEW	SPEC21500S03		15	65	2.7	16	45	48	115	
NEW	SPEC21500S05		15	83	2.7	16	63	48	133	
NEW	SPEC21510S03		15.1	65	2.7	16	45	48	115	
NEW	SPEC21510S05		15.1	83	2.7	16	63	48	133	
NEW	SPEC21550S03		15.5	65	2.8	16	45	48	115	
NEW	SPEC21550S05		15.5	83	2.8	16	63	48	133	
NEW	SPEC21580S03		15.8	65	2.9	16	45	48	115	
NEW	SPEC21580S05		15.8	83	2.9	16	63	48	133	
NEW	SPEC21600S03		16	65	2.9	16	45	48	115	
NEW	SPEC21600S05		16	83	2.9	16	63	48	133	
NEW	SPEC21650S03		16.5	73	3	18	51	48	123	
NEW	SPEC21650S05		16.5	93	3	18	71	48	143	
NEW	SPEC21680S03		16.8	73	3.1	18	51	48	123	
NEW	SPEC21680S05		16.8	93	3.1	18	71	48	143	
NEW	SPEC21700S03		17	73	3.1	18	51	48	123	
NEW	SPEC21700S05		17	93	3.1	18	71	48	143	
NEW	SPEC21750S03		17.5	73	3.2	18	51	48	123	
NEW	SPEC21750S05		17.5	93	3.2	18	71	48	143	
NEW	SPEC21780S03		17.8	73	3.2	18	51	48	123	
NEW	SPEC21780S05		17.8	93	3.2	18	71	48	143	
NEW	SPEC21790S03		17.9	73	3.3	18	51	48	123	
NEW	SPEC21790S05		17.9	93	3.3	18	71	48	143	
NEW	SPEC21800S03		18	73	3.3	18	51	48	123	
NEW	SPEC21800S05		18	93	3.3	18	71	48	143	
NEW	SPEC21830S03		18.3	79	3.3	20	55	50	131	
NEW	SPEC21830S05		18.3	101	3.3	20	77	50	153	
NEW	SPEC21850S03		18.5	79	3.4	20	55	50	131	
NEW	SPEC21850S05		18.5	101	3.4	20	77	50	153	
NEW	SPEC21880S03		18.8	79	3.4	20	55	50	131	
NEW	SPEC21880S05		18.8	101	3.4	20	77	50	153	
NEW	SPEC21900S03		19	79	3.5	20	55	50	131	
NEW	SPEC21900S05		19	101	3.5	20	77	50	153	
NEW	SPEC21950S03		19.5	79	3.5	20	55	50	131	
NEW	SPEC21950S05		19.5	101	3.5	20	77	50	153	
NEW	SPEC21980S03		19.8	79	3.6	20	55	50	131	
NEW	SPEC21980S05		19.8	101	3.6	20	77	50	153	
NEW	SPEC22000S03		20	79	3.6	20	55	50	131	
NEW	SPEC22000S05		20	101	3.6	20	77	50	153	

EI20 鎢鋼平鑽系列

EI20 Carbide Flat Drill Series



180°
水平排屑
Horizontal Chip Removal



全新E300材質

Brand New E300 Material

高剛性、耐磨耗、耐高溫
*High rigidity, Wear resistance
and High temperature resistance*

✓ 適應各式高速CNC銑削加工。

Suitable for various
high-speed CNC milling
processes.

採用德國WALTER 五軸機研磨生產

Produced by German
WALTER five-axis machine
研磨尺寸精準且穩定
Dimension is precise and stable

✓ 加工不平整表面工件等多用途
穩定性佳、精度高、效能佳。

Processing workpieces with
uneven surfaces and other
multi-purpose.
Good stability, high precision
and good performance.

✓ 加工完成後底部可形成平面。
After processing is completed,
the bottom can be formed into
a flat surface.

特殊塗層可加工
Special Coating for


合金鋼
Alloy Steel

碳鋼
Carbon Steel

不鏽鋼
Stainless Steel

尺寸齊全 歡迎詢問

Complete sizes, welcome to inquire


EI20 鎢鋼平鑽
 Carbide Flat Drill


	產品型號 Model No	在庫 Stock	切削直徑	鑽徑	柄部直徑	可使用長度	排屑槽長度	刀徑長度	全長	價格 Price
			DC	DN	DCON	LU	LCF	LUX	OAL	
NEW	EI20200S02		2	1.9	4	6	8	8.3	50	
NEW	EI20210S02		2.1	2	4	6.3	8.4	8.7	50	
NEW	EI20220S02		2.2	2.1	4	6.6	8.8	9.1	50	
NEW	EI20230S02		2.3	2.2	4	6.9	9.2	9.5	50	
NEW	EI20240S02		2.4	2.3	4	7.2	9.6	9.9	50	
NEW	EI20250S02		2.5	2.4	4	7.5	10	10.5	50	
NEW	EI20260S02		2.6	2.5	4	7.8	10.4	11.1	50	
NEW	EI20270S02		2.7	2.6	4	8.1	10.8	11.7	50	
NEW	EI20280S02		2.8	2.7	4	8.4	11.2	12.2	50	
NEW	EI20290S02		2.9	2.8	4	8.7	11.6	12.8	50	
NEW	EI20300S02		3	2.9	6	9	12	12.3	50	
NEW	EI20310S02		3.1	3	6	9.3	12.4	12.7	50	
NEW	EI20320S02		3.2	3.1	6	9.6	12.8	13.1	50	
NEW	EI20330S02		3.3	3.2	6	9.9	13.2	13.5	50	
NEW	EI20340S02		3.4	3.3	6	10.2	13.6	13.9	50	
NEW	EI20350S02		3.5	3.4	6	10.5	14	14.3	50	
NEW	EI20360S02		3.6	3.5	6	10.8	14.4	14.9	50	
NEW	EI20370S02		3.7	3.6	6	11.1	14.8	15.5	50	
NEW	EI20380S02		3.8	3.7	6	11.4	15.2	16	50	
NEW	EI20390S02		3.9	3.8	6	11.7	15.6	16.6	50	
NEW	EI20400S02		4	3.9	6	12	16	17.2	50	
NEW	EI20410S02		4.1	4	6	12.3	16.4	17.8	60	
NEW	EI20420S02		4.2	4.1	6	12.6	16.8	18.4	60	
NEW	EI20430S02		4.3	4.2	6	12.9	17.2	18.9	60	
NEW	EI20440S02		4.4	4.3	6	13.2	17.6	19.5	60	
NEW	EI20450S02		4.5	4.4	6	13.5	18	20.1	60	
NEW	EI20460S02		4.6	4.5	6	13.8	18.4	20.7	60	
NEW	EI20470S02		4.7	4.6	6	14.1	18.8	21.3	60	
NEW	EI20480S02		4.8	4.7	6	14.4	19.2	21.8	60	
NEW	EI20490S02		4.9	4.8	6	14.7	19.6	22.4	60	
NEW	EI20500S02		5	4.9	6	15	20	23	60	
NEW	EI20510S02		5.1	5	6	15.3	20.4	23.6	60	
NEW	EI20520S02		5.2	5.1	6	15.6	20.8	24.2	60	

※ 請接下頁。 ※ Continued on next page.



EI20

鎢鋼平鑽
Carbide Flat Drill

NEW	產品型號 Model No	在庫 Stock	切削直徑	鑽徑	柄部直徑	可使用長度	排屑槽長度	刀徑長度	全長	價格 Price
			DC	DN	DCON	LU	LCF	LUX	OAL	
NEW	EI20530S02		5.3	5.2	6	15.9	21.2	24.7	60	
NEW	EI20540S02		5.4	5.3	6	16.2	21.6	25.3	60	
NEW	EI20550S02		5.5	5.4	6	16.5	22	25.9	60	
NEW	EI20560S02		5.6	5.5	6	16.8	22.4	26.5	60	
NEW	EI20570S02		5.7	5.6	6	17.1	22.8	27.1	60	
NEW	EI20580S02		5.8	5.7	6	17.4	23.2	27.6	60	
NEW	EI20590S02		5.9	5.8	6	17.7	23.6	28.2	60	
NEW	EI20600S02	●	6	5.9	6	18	24	28.8	60	
NEW	EI20610S02		6.1	6	8	18.3	24.4	27.4	75	
NEW	EI20620S02		6.2	6.1	8	18.6	24.8	28	75	
NEW	EI20630S02		6.3	6.2	8	18.9	25.2	28.5	75	
NEW	EI20640S02		6.4	6.3	8	19.2	25.6	29.1	75	
NEW	EI20650S02		6.5	6.4	8	19.5	26	29.7	75	
NEW	EI20660S02		6.6	6.5	8	19.8	26.4	30.3	75	
NEW	EI20670S02		6.7	6.6	8	20.1	26.8	30.9	75	
NEW	EI20680S02		6.8	6.7	8	20.4	27.2	31.4	75	
NEW	EI20690S02		6.9	6.8	8	20.7	27.6	32	75	
NEW	EI20700S02		7	6.9	8	21	28	32.6	75	
NEW	EI20710S02		7.1	7	8	21.3	28.4	33.2	75	
NEW	EI20720S02		7.2	7.1	8	21.6	28.8	33.8	75	
NEW	EI20730S02		7.3	7.2	8	21.9	29.2	34.3	75	
NEW	EI20740S02		7.4	7.3	8	22.2	29.6	34.9	75	
NEW	EI20750S02		7.5	7.4	8	22.5	30	35.5	75	
NEW	EI20760S02		7.6	7.5	8	22.8	30.4	36.1	75	
NEW	EI20770S02		7.7	7.6	8	23.1	30.8	36.7	75	
NEW	EI20780S02		7.8	7.7	8	23.4	31.2	37.2	75	
NEW	EI20790S02		7.9	7.8	8	23.7	31.6	37.8	75	
NEW	EI20800S02		8	7.9	8	24	32	38.4	75	
NEW	EI20810S02		8.1	8	10	24.3	32.4	37	80	
NEW	EI20820S02		8.2	8.1	10	24.6	32.8	37.6	80	
NEW	EI20830S02		8.3	8.2	10	24.9	33.2	38.1	80	
NEW	EI20840S02		8.4	8.3	10	25.2	33.6	38.7	80	
NEW	EI20850S02		8.5	8.4	10	25.5	34	39.3	80	

※ 請接下頁。 ※ Continued on next page.

	產品型號 Model No	在庫 Stock	切削直徑	頸徑	柄部直徑	可使用長度	排屑槽長度	刀徑長度	全長	價格 Price
			DC	DN	DCON	LU	LCF	LUX	OAL	
NEW	EI20860S02		8.6	8.5	10	25.8	34.4	39.9	80	
NEW	EI20870S02		8.7	8.6	10	26.1	34.8	40.5	80	
NEW	EI20880S02		8.8	8.7	10	26.4	35.2	41	80	
NEW	EI20890S02		8.9	8.8	10	26.7	35.6	41.6	80	
NEW	EI20900S02		9	8.9	10	27	36	42.2	80	
NEW	EI20910S02		9.1	9	10	27.3	36.4	42.8	80	
NEW	EI20920S02		9.2	9.1	10	27.6	36.8	43.4	80	
NEW	EI20930S02		9.3	9.2	10	27.9	37.2	43.9	80	
NEW	EI20940S02		9.4	9.3	10	28.2	37.6	44.5	80	
NEW	EI20950S02		9.5	9.4	10	28.5	38	45.1	80	
NEW	EI20960S02		9.6	9.5	10	28.8	38.4	45.7	80	
NEW	EI20970S02		9.7	9.6	10	29.1	38.8	46.3	80	
NEW	EI20980S02		9.8	9.7	10	29.4	39.2	46.8	80	
NEW	EI20990S02		9.9	9.8	10	29.7	39.6	47.4	80	
NEW	EI21000S02		10	9.9	10	30	40	48	80	
NEW	EI21010S02		10.1	10	12	30.3	40.4	46.6	100	
NEW	EI21020S02		10.2	10.1	12	30.6	40.8	47.2	100	
NEW	EI21030S02		10.3	10.2	12	30.9	41.2	47.7	100	
NEW	EI21040S02		10.4	10.3	12	31.2	41.6	48.3	100	
NEW	EI21050S02		10.5	10.4	12	31.5	42	48.9	100	
NEW	EI21060S02		10.6	10.5	12	31.8	42.4	49.5	100	
NEW	EI21070S02		10.7	10.6	12	32.1	42.8	50.1	100	
NEW	EI21080S02		10.8	10.7	12	32.4	43.2	50.6	100	
NEW	EI21090S02		10.9	10.8	12	32.7	43.6	51.2	100	
NEW	EI21100S02		11	10.9	12	33	44	51.8	100	
NEW	EI21110S02		11.1	11	12	33.3	44.4	52.4	100	
NEW	EI21120S02		11.2	11.1	12	33.6	44.8	53	100	
NEW	EI21130S02		11.3	11.2	12	33.9	45.2	53.5	100	
NEW	EI21140S02		11.4	11.3	12	34.2	45.6	54.1	100	
NEW	EI21150S02		11.5	11.4	12	34.5	46	54.7	100	
NEW	EI21160S02		11.6	11.5	12	34.8	46.4	55.3	100	
NEW	EI21170S02		11.7	11.6	12	35.1	46.8	55.9	100	
NEW	EI21180S02		11.8	11.7	12	35.4	47.2	56.4	100	
NEW	EI21190S02		11.9	11.8	12	35.7	47.6	57	100	
NEW	EI21200S02		12	11.9	12	36	48	57.6	100	

鎢鋼鑽頭、中心出水鎢鋼鑽頭、鎢鋼平鑽 切削參數

The Cutting Data For Carbide Drill and Carbide Drill With Coolant and Carbide Flat Drill

被加工材質 Material 鋼 Steel 合金鋼 Alloy Steel 碳鋼 Carbon Steel 不鏽鋼 Stainless steel 鑄鐵 Cast Iron

直徑 (mm) Shank	鑄鐵 Cast Iron K		合金鋼、碳鋼 P Alloy Steel、Carbon Steel		不鏽鋼 M Stainless Steel	
	鋼 P Steel					
	進給速度 f (mm/rev)	轉速 n (min)	進給速度 f (mm/rev)	轉速 n (min)	進給速度 f (mm/rev)	轉速 n (min)
2	0.06	6300	0.06	6300	0.04	4800
3	0.08	4200	0.08	4200	0.07	3200
4	0.1	3200	0.1	3200	0.07	2400
5	0.14	2600	0.14	2600	0.1	1900
6	0.15	2100	0.15	2100	0.1	1600
7	0.16	1800	0.16	1800	0.12	1400
8	0.18	1600	0.18	1600	0.14	1200
9	0.2	1400	0.2	1400	0.14	1100
10	0.2	1300	0.2	1300	0.14	950
11	0.2	1150	0.2	1150	0.18	870
12	0.2	1100	0.2	1100	0.18	800
14	0.2	900	0.2	900	0.18	680
16	0.2	800	0.2	800	0.18	600
20	0.2	650	0.2	650	0.18	480

鎢鋼鉋刀識別系統

Carbide Reamer Identification System

RL-S M M 3 0300 XXX



1 特徵 Feature

記號 Symbol	特徵 Feature
RL	鉋刀左螺旋 Reamer Left Screw

2 螺旋角 Helix Angle

記號 Symbol	角度 Angle
S	8°

3 材質 Grade

記號 Symbol	材質 Grade
E	E300
M	M500
P	P500

4 用途 Application


記號 Symbol	說明 Explanation
M	平刀 Square

7 其他 Other

記號 Symbol	說明 Explanation
L1	特殊切刃長度 Special Flute Length
L2	特殊可使用長度 Special Length
特殊全長 (mm) Special L.F	E:1.75 H:100 M:150

規格圖標指南

Specification Icon Guide

圖標 Icon	說明 Explanation	圖標 Icon	說明 Explanation
	超微粒子超硬合金 Micro Grain Carbide		材質 Grade
	含鈷量 Cobalt Content		AlTiN 鋁鈦氮塗層 TiSiN 矽鈦塗層
	可被切削材硬度 Working Hardness		螺旋角度 Helix Angle

RL-SMM30000 series

3 刃右刃左螺旋鎢鋼鉸刀

3 Right Flute Left Helical Carbide Reamer

採用頸徑小於刃徑設計，可進行深孔修磨
The neck diameter is smaller than the flute diameter, which is able to grind deep hole.

右刃左螺旋對於修磨切痕孔特別具有加工安定性
Right Flute Left Helix particularly has stable processing for grinding the hole wall.

採用8°螺旋角設計利於排屑順暢
8° helix angle design is good for smooth chip removal.

全新M500材質全鎢鋼棒材加上高鋁鈦塗層
適用於合金鋼、不鏽鋼及鑄鐵等材質加工
皆擁有良好的深孔修磨表現

Brand new M500 material full carbide rod, and high-aluminum titanium coating.
Suitable for alloy steel, stainless steel, cast iron.
All have good deep hole grinding performance

適用材質 Material


鋼 Steel

不鏽鋼 Stainless steel

鑄鐵 Cast Iron



尺寸齊全 歡迎詢問
Complete sizes, welcome to inquire

RL-SMM30000 3刃右左螺旋鎢鋼鉸刀
 3 Flute Left Spiral Carbide Reamer


 新品上市
 New Arrival

產品型號 Model No	在庫 Stock	切削直徑 DC +0.005 0	頭徑 DN	頂端至肩部尺寸差 PL	柄部直徑 DCON	刀頭長度 LH	工作懸伸長度 LPR	全長 OAL	價格 Price
NEW RL-SMM30300L126L250E1		3	2.8	0.5	4	26	50	75	
NEW RL-SMM30310L126L250E1		3.1	2.9	0.5	4	26	50	75	
NEW RL-SMM30320L126L250E1		3.2	3	0.5	4	26	50	75	
NEW RL-SMM30330L126L250E1		3.3	3.1	0.5	4	26	50	75	
NEW RL-SMM30340L126L250E1		3.4	3.2	0.5	4	26	50	75	
NEW RL-SMM30350L126L250E1		3.5	3.3	0.5	4	26	50	75	
NEW RL-SMM30360L126L250E1		3.6	3.4	0.5	4	26	50	75	
NEW RL-SMM30370L126L250E1		3.7	3.5	0.5	4	26	50	75	
NEW RL-SMM30380L126L250E1		3.8	3.6	0.5	4	26	50	75	
NEW RL-SMM30390L126L250E1		3.9	3.7	0.5	4	26	50	75	
NEW RL-SMM30400L126L250E1		4	3.8	0.5	4	26	50	75	
NEW RL-SMM30410L126L250E1		4.1	3.9	0.5	6	26	50	75	
NEW RL-SMM30420L126L250E1		4.2	4	0.5	6	26	50	75	
NEW RL-SMM30430L126L250E1		4.3	4.1	0.5	6	26	50	75	
NEW RL-SMM30440L126L250E1		4.4	4.2	0.5	6	26	50	75	
NEW RL-SMM30450L126L250E1		4.5	4.3	0.5	6	26	50	75	
NEW RL-SMM30460L126L250E1		4.6	4.4	0.5	6	26	50	75	
NEW RL-SMM30470L126L250E1		4.7	4.5	0.5	6	26	50	75	
NEW RL-SMM30480L126L250E1		4.8	4.6	0.5	6	26	50	75	
NEW RL-SMM30490L126L250E1		4.9	4.7	0.5	6	26	50	75	
NEW RL-SMM30500L126L250E1		5	4.9	0.5	6	26	50	75	



鎢鋼鉸刀切削參數

The Cutting Data For Carbide Reamer

被加工材質 Material 鋼
Steel 不鏽鋼
Stainless steel 鑄鐵
Cast Iron

刃數 Flute	直徑 (mm) Shank	P 鋼 Steel		M 不鏽鋼 Stainless Steel		K 鑄鐵 Cast	
		進給速度 f (mm/rev)	轉速 n (min)	進給速度 f (mm/rev)	轉速 n (min)	進給速度 f (mm/rev)	轉速 n (min)
3	4	120	1200	100	1000	120	1200
	6	80	800	65	650	80	800