

S-OGM 2000 微小徑 2 刃鎢鋼立銑刀
 Micro Diameter 2 Flute Carbide End Mill


 新品上市
 New Arrival


 MG



 L10
 0.05
























 CO
 12%


 HRC
 55


 G
 300


 40


 Altim


	產品型號 Model No	在庫 Stock	切削直徑 DC	切削長度 APMX	柄部直徑 DCON	標準全長 LF	價格 Price
	S-OGM2003	●	0.3	1.2	4	50	
	S-OGM2004		0.4	1.6	4	50	
	S-OGM2005		0.5	2	4	50	
	S-OGM2006		0.6	2.4	4	50	
	S-OGM2007		0.7	2.8	4	50	
	S-OGM2008		0.8	3.2	4	50	
	S-OGM2009		0.9	3.6	4	50	
	S-OGM2010		1	4	4	50	
	S-OGM2011		1.1	4.4	4	50	
	S-OGM2012		1.2	4.8	4	50	
	S-OGM2013		1.3	5.2	4	50	
	S-OGM2014		1.4	5.6	4	50	
	S-OGM2015		1.5	6	4	50	
	S-OGM2016		1.6	6.4	4	50	
	S-OGM2017		1.7	6.8	4	50	
	S-OGM2018		1.8	7.2	4	50	
	S-OGM2019		1.9	7.6	4	50	
	S-OGM2020		2	8	4	50	
	S-OGM2021		2.1	8.4	4	50	
	S-OGM2022		2.2	8.8	4	50	
	S-OGM2023		2.3	9.2	4	50	
	S-OGM2024		2.4	9.6	4	50	

※ 請接下頁。 ※ Continued on next page.

	產品型號 Model No	在庫 Stock	切削直徑	切刃長度	柄部直徑	標準全長	價格 Price
			DC	APMX	DCON	LF	
NEW	S-OGM2025		2.5	10	4	50	
NEW	S-OGM2026		2.6	10.4	4	50	
NEW	S-OGM2027		2.7	10.8	4	50	
NEW	S-OGM2028		2.8	11.2	4	50	
NEW	S-OGM2029		2.9	11.6	4	50	
NEW	S-OGM2030D6		3	12	6	50	

S-OGM 2000系列切削參數


The Cutting Data For S-OGM 2000 Series

被加工材質 Material 鋼 Steel 不鏽鋼 Stainless steel 鑄鐵 Iron cast


直徑 (mm) Shank		4	6
轉速 n (min)		4800	3100
進給速度 (mm/min) Vf	開槽 Slotted	135	120
	側邊 Side	475	375

切削深度 Cutting depth

開槽 Slotted



側邊 Side



ap : 軸向切削深度 Axial depth of cutting

ae : 徑向切削深度 Radial depth of cutting

DC : 刃徑 Diameter of cutting